

Installation instructions for Corner Slow Feeder (KIT ONLY)

Simple slow feeding for the stable!

With each corner slow kit you should receive:

1 x slow feeder net—with trigger clip attachment

1 x metal bracket

Additional tools needed to install Corner Slow kit :

- Electric Drill with 10mm drill bit
- Minimum of 8 screws to secure the bracket to the wall.
- Raw plugs if drilling into masonry



Securing your net to the feeder

- 1.) Empty your existing feeder of any hay, dust or seeds
- 2.) Drill 15 holes equally spaced across the front of your feeder (approx 10cm apart) see examples in photo 1.
- 3.) Screw the bracket in the corner of the stable with your electric drill place level with the top of the feeder.
- 4.) Connect your clip to the bracket. Place your net inside the feeder and check to see if the pipe needs shortening. The pipe should fit snugly in the corner of the feeder reaching each side of the feeder it should be woven in and out of the net. If the pipe is too long please follow step 4A.
- 4A.) To shorten the pipe pull the bungee out of the pipe, cut the pipe to the desired length, feed the bungee back through. Do not cut the bungee.
- 5.) Thread the bungee back through to the end of the pipe as it was when purchased.
- 6.) attach the net to the front of the feeder with the cable ties through the pre-drill holes.
- 7.) Your feeder should now be securely attached to the front of your corner feeder.



Using the slow stable feeder

flip the net over the front of the feeder and fill with hay— as photo 6

Attach the clip onto the metal bracket and watch it slide to the bottom of the feeder as your horse eats it hay.— photo 7